



Product: 8114 ELS-GUBA

Image	Description
	<p><b>ELS-GUBA</b>            Unterputzgehäuse mit Brand-            schutzabsperriklappe K90</p> <p>Flush mounted casing in flat design for insertion of the ELS fan unit for installation in installation shaft, plaster board systems, wall or ceiling.            With maintenance-free fire protection shutter (K90, 18017), metal discharge spigot and maintenance-free back draught shutter made from stainless steel. Shut-off of fire protection shutter with release of fusible link.            Connection to main line via spiral duct or flexible steel duct.</p> <p>Comfortable electric connection by removable quick plug connector.</p> <p>Discharge spigot (DN 80 mm) to the top, can be positioned to the left or right. Discharge to the back also possible by changing position of spigot. Built-in airtight back draught shutter, maintenance-free.</p> <p>Connectivity for second room ventilation or toilet pan via rinsing tube DN 50/40/30 mm (lateral on the left, right or below).</p> <p>Universal casing made from flame retardant polymer (white), class B2 with embedded turn-locked slots to take up the mounting bracket. Cardboard cover plate included in delivery. dimensions: W/H/D 230x230x89 mm</p> <p>DIBT- Approval no. Z-51.1-193</p>

**Accessories**

Image	Ref.no.	Model	Description	Group
	7328	ELS- APASA	Surface-mounted adapter with side discharge for ELS-GU and ELS-GUBA casing	B