

Air water heater series

FARMER OpenAir 230V



Place to use:

The Farmer OpenAir series water heater is designed to work in an aggressive environment such as:

- car washes,
- stables,
- greenhouses,
- pigsties,
- chicken coops.



Device features:

- has a special GOLD EPOXY coating,
- fan with increased IP degree,
- equipped with a fully opening housing, allowing easy access to the device for maintenance,
- adapted to many different mounting solutions.



	UNIT	FARMER OPENAIR IP66
PRODUCT CODE		WHHCFO-2042
NOMINAL HEATING CAPACITY	kW*	54,3
HEATING CAPACITIES RANGE	kW**	7,5 - 71,6
MAXIMUM AIRFLOW	m³/h	5100
MAXIMUM ISOTHERMAL STREAM RANGE	m	25
NUMBER OF ROWS	pcs.	3
WATER CAPACITY	dm³	3,8
MAXIMUM TEMPERATURE OF HEATING FLUID	°C	120
MAXIMUM PRESSURE OF HEATING FLUID	MPa	1,6
CONNECTORS DIAMETER	cal	3/4
VOLTAGE / FREQUENCY	V/Hz	230/50
NOMINAL MOTOR CURRENT	A	2,2
NOMINAL MOTOR SPEED	rpm	1395
NOMINAL MOTOR POWER	W	500
IP PROTECTION RATING OF MOTOR	-	66
NET WEIGHT	kg	46
NOISE	dB***	66

* for the parameters 90/70 °C and the inlet air temperature 0 °C

** the max. capacity for 120/90 °C, 0 °C the inlet air temperature // the min. capacity for 40/30 °C, 20 °C the inlet air temperature

*** the measurement at the distance of 5 m from the device